

Incoloy heating elements should be used in swimming pools and spa pools. In other heating systems (floor heating, central heating etc.) the surface output of the heating element should not exceed 12W/cm².

Heating elements acid-proof stainless steel AISI 316 2" 230/400V

Item no.	Capacity (kW)	Surface capacity (W/cm ²)	Installed length (mm)
12724	4,5	8,9	355
12733	6,0	8,8	255
127332	6,0	10,5	380
12746	7,5	8,0	330
12756	9,0	8,9	355
127561	3+6	8,7	465
127562	2x4,5	11,1	385

Used in heating systems.



Heating elements acid-proof stainless steel AISI 316 2½" 230/400V

Item no.	Capacity (kW)	Surface capacity (W/cm ²)	Installed length (mm)
12734	6,0	7,5	270
12744	7,5	7,5	330
12754	9,0	7,5	390

Used in heating systems.



Heating elements Incoloy 825 2" 230/400V

Item no.	Capacity (kW)	Surface capacity (W/cm ²)	Installed length (mm)
127044	1,5	6,2	255
127144	3,0	8,5	255
127244	4,5	12,8	255
127344	6,0	17,0	255
127544	9,0	17,7	355
127644	12,0	23,0	355
127754	15,0	29,3	355
127854	18,0	35,1	355

Used in electric heaters for swimming pools and spa pools. Please order 230V or 400V



Heating elements Incoloy 825 2½" 230/400V

Item no.	Capacity (kW)	Surface capacity (W/cm ²)	Installed length (mm)
127143	3,0	8,5	255
127343	6,0	12,8	255
127443	7,5	17,0	330
127543	9,0	17,7	355
127643	12,0	23,0	355
127746	15,0	29,3	355
127846	18,0	35,1	355

Used in electric heaters for swimming pools and spa pools.



Heating elements Incoloy 825 and Nic-Tech 2" 230/400V

Item no.	Capacity (kW)	Surface capacity (W/cm ²)	Installed length (mm)
127144N	3,0	8,5	255
127344N	6,0	17,0	255
127544N	9,0	17,7	355
127644N	12,0	23,0	355
127754N	15,0	29,3	355
127854N	18,0	35,1	355

Used in electric heater titanium for swimming pools and spa pools.

