

Nozzles and outlets

MADE OF ACID PROOF STAINLESS STEEL AISI 316L



Bottom inlet

Item no. Type

126120	CA	Inside thread 1 1/2".
--------	----	-----------------------

The flow can be regulated in eight different positions on the front of the inlet. Capacity flow max 15m³/h.



Bottom inlet nozzle

Item no. Type

12550	A-1	Outside thread 1 1/2".
-------	-----	------------------------

12560	A-2	Outside thread 2".
-------	-----	--------------------

Flow capacity A-1 max 6 m³/h, A-2 max 8 m³/h.



Suction nozzle Classic

Standard

Item no. Type

125821	CA
--------	----

12650	A
-------	---

Capacity flow max 2 m³/h.

Extended

Item no. Type

125826	CA
--------	----

Standard

Item no. Type

125831	CA
--------	----

Extended

Item no. Type

125836	CA
--------	----



Vacuum hose connection Classic

	Pool construction	Concrete blocks construction	Concrete construction	Concrete construction	Fibre glass construction
	In combination with liner 0,75 - 2 mm	With tiles or paint	With tiles or paint.	Without liner	
Lights					
Item no.	Type	Concrete bulding blocks up to 250 mm	Concrete without sealing membrane up to 250 mm	Concrete with cement based sealing membrane up to 250 mm	Composite material (GRP/PP) up to 16 mm
126120	CA	•			
125933	CA-WBS	•			• (+15530132)
125938	A-WBS		•		
1302140	CA-WB	• (+ 112900, 1302145)	• (+ 112900, 1302145)		
125931	CA-WBB	•			• (+ 15530132)
125936	A-WBB		•		
12550	A-1		•	•	
12560	A-2		•	•	
125821	CA				• (+ 15530111)
12650	A		• (+12640)		
125826	CA	•		• (+ 822600)	
125831	CAA		• (+ 12670)		• (+ 15530111)
125836	CA	•		• (+ 822600)	

Wall outlet Maxi



Item no. Type

1302140 CA-WB

Capacity flow max 67 m³/h. Inside thread 2½".



Non leak flange

Accessories

Item no

15530111 Assembly kit inlets/spotlights fibre glass/PP pool

822600 Concrete-kit inlets/spotlights for cement based sealing membrane

15530132 Fixing kit wall and bottom outlet fibre glass/PP pool

13083002 Distance wall and bottom outlet for steel pool

822145 Mounting plate for inlets/spotlights

Non leak flange

12670 Inside and outside thread 1 ½". L = 290 mm.

12675 Inside and outside thread 1 ½". L = 600 mm.

12640 Inside thread 1 ½". L = 255 mm.

126751 Inside and outside thread 2". L = 600 mm.

121952 Outside thread 2". L = 250 mm.

1302145 Wall Outlet Maxi, inside and outside thread 2½" L = 250 mm

Wall and bottom outlet



Item no. Connection side Item no. Connection bottom

125933 CA-WBS

125931 CA-WBB

125938 A-WBS

125936 A-WBB

Capacity flow max 20 m³/h. Inside thread 2".

EPS/ISO blocks construction	Steel panel construction	Wood construction	Wood/concrete construction
Reinforced with concrete in combination with liner 0,75 - 2 mm	In combination with liner 0,75 - 2 mm	In combination with liner 0,75 - 2 mm	In combination with liner 0,75 - 2 mm
Building blocks up to 250 mm	Steel panels up to 3 mm	Plywood 12 mm	Wood 32 - 70 mm Prefabricated concrete 50 - 250 mm
•	•	•	•
•	• (+ 13083002, 2 pc)	•	•
• (+ 112900, 1302145)	•	•	
•	• (+ 13083002, 2 pc)	•	•
	•	•	• (+ 822145)
•			
	•	•	• (+ 822145)
•			